HA65Q/15-11





Model	HA65Q/15-11
Operating pressure	12 to 23 bar
Weight	2.0 kg
Dimensions (H x L x W)	312.0 x 370.2 x 81.2 mm
Load capacity	130 staples
Air consumption	1.7L at 18 bar operating pressure
	A-weight single-event sound power level LWA, 1s, d 93,9 dB A-weight single-event emission sound pressure level at work station LpA, 1s, d 83.3 dB These values are determined and documented in accordance to EN12549;1999+A1:2008
	Vibration characteristic value = 4.45 m/s2 These values are determined and documented in accordance to ISO 28927-13

HN65Q/15-11 is our "The World's 1st High Pressure Q stapler". Max HA65Q/15-11 can fasten harder material panels without staples sticking out and leaving a flat surface. HA65Q/15-11 is 25% faster than 8 bar systems. It has air duster system on which the air volume is adjustable with the pressure button and easy jam clearance system which help to remove jammed staple in magazine without any tools.

Features

Powerful & Clear Flushness



Easy jam clearance



Air duster system






1 71m

38~65mm → ↓ ↓ ↓ 18.8 mm ↓ 11.0mm

Less air consumption makes more staples with Powerlite



Applications PANEL SHEATHING / DECKING



